



0,00m		1,60m		39,80	41,40	Trojnik PEHDØ32/32		
11,5m	PEHDØ32	L=11,5m i=---	1,60m	39,80	41,40	Projektowany natrysk zewn. ECU 50l		
Trojnik PEHDØ40/40								
0,00m		0,00m	1,60m	39,70	41,30	Redukcja PEHDØ40/32		
3,00m		3,00m	1,60m	39,70	41,30	Zmiana trasy o kat 45°		
		L=8,0m i=---						
11,0m			1,60m	39,70	41,30	Zmiana trasy o kat 45°		
	PEHDØ32	L=15,0m i=---						
26,0m			1,60m	39,70	41,30	Zmiana trasy o kat 90°		
28,0m			2,00m	1,60m	39,70	41,30	Zmiana trasy o kat 45°	
30,0m			2,00m	1,60m	39,70	41,30	Projektowany natrysk zewn. ECU 50l	

		Trojnik PEHDØ40/40						
0,00m		0,00m	1,60m	39,70	41,30	Redukcja PEHDØ40/32		
3,00m		3,00m	1,60m	39,70	41,30	Zmiana trasy o kat 45°		
11,0m		L=8,0m i=---	1,60m	39,70	41,30	Zmiana trasy o kat 45°		
26,0m	PEHDØ32	L=15,0m i=---						
28,0m			2,00m	1,60m	39,70	41,30	Zmiana trasy o kat 45°	
30,0m			2,00m	1,60m	39,70	41,30	Projektowany natrysk zewn. ECU 50l	

[illegible]